



University of Pennsylvania
ScholarlyCommons

Departmental Papers (ESE)

Department of Electrical & Systems Engineering

2014

Cellular Decomposition and Classification of a Hybrid System

Aaron M. Johnson
University of Pennsylvania

Daniel E. Koditschek
University of Pennsylvania, kod@seas.upenn.edu

Follow this and additional works at: https://repository.upenn.edu/ese_papers

 Part of the [Electrical and Computer Engineering Commons](#), and the [Systems Engineering Commons](#)

Recommended Citation

Aaron M. Johnson and Daniel E. Koditschek, "Cellular Decomposition and Classification of a Hybrid System", *Northeast Robotics Colloquium* . January 2014.

This paper is posted at ScholarlyCommons. https://repository.upenn.edu/ese_papers/873
For more information, please contact repository@pobox.upenn.edu.

Cellular Decomposition and Classification of a Hybrid System

Abstract

Robots are often modeled as hybrid systems providing a consistent, formal account of the varied dynamics associated with the loss and gain of kinematic freedom as a machine impacts and breaks away from its environment.

Disciplines

Electrical and Computer Engineering | Engineering | Systems Engineering

Cellular Decomposition and Classification of a Hybrid System

Aaron M. Johnson and D. E. Koditschek*

Robots are often modeled as hybrid systems providing a consistent, formal account of the varied dynamics associated with the loss and gain of kinematic freedom as a machine impacts and breaks away from its environment [1]. This hybrid structure induces an abstract simplicial complex indexed by the active contact constraints, where each vertex in the complex is a single constraint. This complex provides a concise description of the possible edges of the hybrid system through impacts – they must lie in the closure of the star of the current cell (i.e. $(I, J) \in \Gamma \Leftrightarrow J \in \text{ClSt } I$). This structure is in some sense dual to the “ground reaction complex”, [2], wherein constraints reduce dimension and the equivalent adjacency property is instead the star of the closure (i.e. $(I, J) \in \Gamma \Leftrightarrow J \in \text{St Cl } I$). Under either formulation, sequences of contact conditions (“letters”) define smooth families of executions (“words”). Points of discontinuity lie within the boundaries between words, but in certain cases the evaluation can still be continuous over an open set including these boundaries, even though the associated words change abruptly. We present examples of these “convergent” and “divergent” word boundaries.

REFERENCES

- [1] A. M. Johnson, S. A. Burden, and D. E. Koditschek, “A hybrid systems model for simple manipulation and self-manipulation systems,” 2014, in prep.
- [2] A. M. Johnson and D. E. Koditschek, “Toward a vocabulary of legged leaping,” in *Proceedings of the 2013 IEEE Intl. Conference on Robotics and Automation*, May 2013, pp. 2553–2560.

Presented as a poster at the 2014 Northeast Robotics Colloquium, Providence, RI. This work was sponsored by the ARL/GDRS RCTA consortium.

*Electrical and Systems Engineering Department, School of Engineering and Applied Sciences, University of Pennsylvania, 200 S. 33rd St, Philadelphia, PA 19104, USA, {aaronjoh, kod}@seas.upenn.edu